



CANVAS CABINS

Outstanding Wall Tents

5135 US Hwy 12E, Garrison, MT 59731

971-219-9000 * 503-487-7404

About Your New Spotted Owl Tent Stove

Your stove is made of cold steel, but there's no extra charge for the rust. If you don't want it to rust, clean it with lacquer thinner and paint it with a high temp paint available at the hardware store. Don't paint the water reservoir as it is made of stainless steel. Also don't let the water reservoir boil dry as it is not welded but is soldered with lead free solder.

Your Spotted Owl stove has reinforcing in it to keep the warping down, (flat enough to cook on), but it will still warp. If it doesn't you bring it back and we'll refund your money.

The bottom tray is part of the support structure on the stove. It is designed to be a tight fit between the bolt heads and the cut outs on the tray.

If your stove jack is in the side of your tent, put a 45 degree elbow right on the stove, run 3 lengths of pipe out the tent at a 45 degree angle and put the second 45 degree elbow at the top so it points straight up. Wire the chimney to the eave pole to hold it up or if you don't have our pole set, wire it to the grommets on the eave of your tent.

Don't run the chimney with a length going straight up, a 90 degree going out and another 90 degree going up. This is twice the bends, and it won't draw as well, and you'll have to build something outside to hold it up.

On the collar of your stove there are two ears with holes drilled in them with a wire attached to one of them. Run this wire outside the pipe, through the stove jack in your tent, and over the top elbow after you install the "T" cap. Now pull it snug and bring it back down the other side of the pipe and fasten it to the other ear on the stove collar. This is to keep the chimney from coming apart in the wind.

Enjoy,

Bob & Cliff